



We are specialists
in advanced
heating systems
and solutions



2023

PRODUCTS THAT CREATE EXPERIENCES.

The reliability of good work.

The second group of products are listed in AIS KLIMA, a sub-brand offering **innovative solutions** for underfloor heating systems.

We have 3 different UFH Systems, each one of them developed to satisfy the customers' different requirements according to the type of installation.

AIS KLIMA solutions:

- Safer
- Simpler
- More sustainable



PRODUCTS THAT CREATE VALUE:

- Innovative products.
- Wide range of solutions.
- Energy efficient solutions.
- Save on installation time.

Our AIS KLIMA solutions:



AIS KLETT PANEL AND TUBING
SELF-ADHESIVE SYSTEM



AIS NUBS PANEL AND
TUBING SYSTEM



AIS ELECTRIC ELECTRICAL
MESH SYSTEM





AIS KLETT self-adhesive system

The under floor heating system that liberates your application.

The AIS Klett Self-adhesive system enables an **efficient, comfortable and clean installation.**

AIS Klett Self-adhesive system set:

AIS Klett Panel: smooth panel with insulating base (EPS and graphite) with a surface layer of self-adherent fibres.

AIS Klett Tubing: 7-layer tubing including self-adhesive Velcro taping. Manufactured with PERT material (heat resistant polyethylene), which provides great flexibility and an EVOH intermediate layer that acts as a barrier against oxygen diffusion.

AIS KLETT SELF-ADHESIVE SYSTEM: *the underfloor heating system that enables the pipe to be fitted through simple contact.*



Supply of panel in a roll that enables quick installation.



EPS and graphite insulating materials



Circuit-free design.



Without tools



System meets the thermal insulation requirements according to UNE EN 1264:2022 standard.



Self-attaching system: immediate installation, saving up to 40% of installation time.



High use of the insulating panel: reduction of cuts and greater profitability.



AIS Klett graphite systems 25mm and 40mm certified by Aenor according to UNE EN 1264:2022 standard.



AIS KLIMA

AIS Klett SELF-ADHESIVE SYSTEM

AIS KLETT INSULATION PANEL



Klett Graphite insulation panel. G EPS graphite panel roll for self-adhesive tubing




Reference	Description	Dimensions	Minimum sales pcs
412.07825N	<ul style="list-style-type: none"> For mezzanines, on heated premises. Thermal and acoustic insulation impact and airborne noise 	25-2 mm. 12 x 1 m. R-value = 0,80 m ² K/W W ΔLw = 26 dB	12m ²
412.12540N	<ul style="list-style-type: none"> For basements on the ground, on NON-heated premises. Thermal insulation 	40-2mm. 8 x 1m. R-value= 1,25 m ² K/W	8m ²

Klett White insulation panel. EPS white panel roll for self-adhesive tubing



412.05625N	<ul style="list-style-type: none"> Thermal and acoustic insulation impact and airborne noise 	25-2mm. 12 x 1m. R-value= 0,56 m ² K/W ΔLw = 28 dB	12m ²
-------------------	---	---	------------------

AIS UltraSlim panel roll.



412.303046	<ul style="list-style-type: none"> Ultra-low profile especially suitable for renovations. With adhesive layer, for direct installation on existing surface 	20 x 1,05m. Thickness: 2mm	21m ²
-------------------	--	-------------------------------	------------------

AIS KLETT PIPE



Reference	Description	Dimensions	Minimum sales pcs	Pallet or pcs per boxes
116.16240	<ul style="list-style-type: none"> 7-layer tube with anti-oxygen diffusion barrier, application class 5: underfloor heating and low-temperature radiators. 	16 x 2,00	240m	2880m
116.16500		16 x 2,00	500m	3000m



AIS KLIMA Nubs System

The most flexible AIS KLIMA solution for your installation.


The AIS Nubs system has individual panels for your **tool-free installation**.

AIS Nubs system set:

AIS Nubs Panel: available with EPS finish plasticized or rigid thermoformed EPS.

AIS PERT-EVOH pipe: 5-layer pipe manufacture in PERT material (temperature resistant polyethylene) which provides great flexibility and an EVOH intermediate layer that acts as a barrier against oxygen diffusion.

AIS NUBS SYSTEM: *the most durable AIS KLIMA system for installation.*



Its raised height improves heat distribution.



Greater mechanical resistance to compression and footsteps during installation.



Waterproof panel with a protective layer that prevents the passage of moisture from the mortar, for UNE EN 1264:2022 standard.



Fast and tool-free installation: Nubs designed to increase the attaching of the pipe to the panel without the need for clamps.



AIS KLIMA

AIS KLIMA NUBS SYSTEM

AIS NUBS INSULATION PANELS



Reference	Dimensions	Minimum sales pcs
-----------	------------	-------------------

Nubs thermoformed EPS insulation panel

411.2542	1400 x 800 mm (1,12m ²) Base thickness= 20mm. Total thickness= 42mm. R _{λ,ins} *=0,59 m ² K/W	11,2m ²
----------	--	--------------------



Nubs plasticized EPS insulation panel

411.2546	1350 x 750mm (1,01m ²) Base thickness= 17mm. Total thickness= 46mm. R _{λ,ins} *=0,48 m ² K/W	14,17m ²
----------	---	---------------------

411.2563	1350 x 750mm (1,01m ²) Base thickness= 34mm. Base thickness= 63mm. R _{λ,ins} *=0,97 m ² K/W	9,11m ²
----------	--	--------------------

*Resistance calculated according to UNE EN 1264:2022 standard



NEW

Nubs thermoformed panel without insulation

411.0020	1400 x 800 mm (1,12 m ²) Thickness = 20mm.	22,4m ²
----------	--	--------------------

AIS KLIMA PIPE



Reference	Dimensions	Minimum sales pcs	Pallet or pcs per box
-----------	------------	-------------------	-----------------------

PE-RT EVOH pipe, natural white colour, with anti-oxygen diffusion barrier.

117.16240	16 x 2,00	240m	2880m
-----------	-----------	------	-------

117.16500	16 x 2,00	500m	3000m
-----------	-----------	------	-------



Reference	Dimensions	Minimum sales pcs	Pallet or pcs per box
-----------	------------	-------------------	-----------------------

PE-Xa EVOH pipe, natural white colour, with anti-oxygen diffusion barrier.

113.20500	20 x 2,00	500m	3500m
-----------	-----------	------	-------



Reference	Description	Dimensions	Minimum sales pcs
-----------	-------------	------------	-------------------

Multilayer Pipe

101.16500	<ul style="list-style-type: none"> With anti-oxygen diffusion barrier PERT-AL-PERT pipe. 	16 x 2,00	3000m
-----------	--	-----------	-------



AIS Electric System


AIS KLIMA Heating system.

AIS Electric replaces the pipe with a cable for heat distribution, and the panel with an electric mesh, which allows it to **reach a higher temperature in less time.**

AIS Electric system set:

Available in **self-adhesive mesh or aluminium blanket in roll attached to a 3mm-thick heat conducting wire.**

AIS ELECTRIC SYSTEM: *speed and dynamism in your installation.*



AIS KLIMA solution with very small thicknesses



Quick installation; self-adhesive mesh supplied in rolls.



Ideal for heating small rooms.



Quick reaction time: enables for maximum thermal comfort in the shortest possible time



AIS KLIMA

AIS ELECTRIC SYSTEM

ELECTRIC MESH ROLL

AIS KLIMA



Reference	Description	Dimensión	Ud. mínima de venta
Electric underfloor heating.			
413.160304	<ul style="list-style-type: none"> Mesh roll Power 160 W m², Installation in mortar and under tile flooring. 	4 m ² (length 8m; wide 0.5m) 3mm cable Available from 0.5m ² to 15m ² (on request, please check)	1 pcs.
Under heating electrical system.			
413.140305	<ul style="list-style-type: none"> Aluminium blanket roll. Power 140 W m². Installation on foam and under wooden or carpet flooring. 	5 m ² (length 10m; wide 0.5m). 3mm cable Available from 1m ² to 12m ² (on request, please check)	1 pcs.



AIS KLIMA Common Features



AIS KLIMA

AIS KLIMA **COMMON FEATURES**

INSTALLATION ACCESSORIES

Reference	Dimensions	Minimum sales pcs
-----------	------------	-------------------



AIS KLIMA Panel joint adhesive tape

412.4866

Roll 48mm x 66m

1 pcs.



Anti-humidity film

420.5012

4mx25m. Thickness 0,2mm.

100m2



Self-adhesive edging strip with plastic apron

420.150850

150mm x 8mm x 50m

50m



Guiding elbow for pipe

412.1418

14mm-18mm

25 pcs.

412.2022

20mm

25 pcs.

Reference	Minimum sales pcs
-----------	-------------------



Fluidizing additive for mortar. 25 Kg

460.1080

1 pcs.



AIS KLIMA Regulation and Control

THERMOSTATIC REGULATION

Reference	Descripción	Dimensions	Minimum sales pcs
-----------	-------------	------------	-------------------

Programmable digital thermostat



423.220003

- For electric underfloor heating.
- Includes soil probe and temperature limitation.

80,5 x 80,5 x
42,5mm.

1 pcs

Reference	Dimensions	Minimum sales pcs
-----------	------------	-------------------

Wired room thermostat



421.0014

- Heating only.
- 230V.
- Installation of 3x1.5mm hose is recommended.

1 pcs.



Wired room thermostat F-C

422.3012

- Heating/Cooling.
- 230V.
- Installation of 4x1.5mm hose is recommended.

1 pcs.

Reference	Description	Minimum sales pcs
-----------	-------------	-------------------

Wired programmable digital thermostat



422.34230

- Heating/Cooling
- 230V
- LCD Screen 58x34mm.
- Programming for weekdays, weekends or entire week.
- Up to 28 memories.
- Installation of 4x1.5mm hose is recommended.

1 pcs.

Wireless programmable digital thermostat



422.5080

- Heating/Cooling.
- Battery powered.
- LCD Screen 58x34mm.
- Local and remote operation by webApp.

1 pcs.

Wireless room thermostat



422.5081

- Heating/Cooling.
- Battery powered.
- Local and remote operation by webApp




1 pcs.




THERMOSTATIC REGULATION

Reference	Description	Minimum sales pcs
	<p>Thermostatic actuator</p> <p>421.1114L</p> <ul style="list-style-type: none"> For regulating the underfloor heating-cooling circuit. Includes connector and cable. 230V. 	1 pcs.
	<p>Thermostatic actuator with micro</p> <p>422.5090</p> <ul style="list-style-type: none"> Thermostatic actuator 230 V 4 wires with micro. For regulating the underfloor heating-cooling circuit. Includes connector and cable. 230V. 	1 pcs.
	<p>Wired connection panel. Supply 230 V.</p> <p>422.3222 For 6 areas- 12 actuators</p> <hr/> <p>422.3223 For 10 areas- 18 actuators</p>	1 pcs. 1 pcs.
	<p>Wireless connection panel</p> <p>422.5073</p> <ul style="list-style-type: none"> Wireless. 4 areas - 6 actuators. Supply 230 V. Control by webApp. <hr/> <p>422.5074</p> <ul style="list-style-type: none"> Wireless. 8 areas - 12 actuators. Supply 230 V. Control by webApp. 	1 pcs. 1 pcs.

HYDRAULIC REGULATION

Reference	Description	Dimensions
	<p>2-way motorized zone valve 230V</p> <p>422.6223034 3/4" M-M</p> <hr/> <p>422.62230100 1" M-M</p>	1 pcs. 1 pcs.
	<p>Differential pressure by-pass valve 0.25bar</p> <p>422.6025100 1" M-M</p>	1 pcs.
	<p>Direct supply and mixing unit at fixed point</p> <p>422.6000 -</p>	1 pcs





AIS KLIMA Distribution

MANIFOLDS AND CABINETS

Reference	Dimensions	Minimum sales pcs
-----------	------------	-------------------

Standard manifold cabinet




422.435110	43x71x11-15 cm (2-3 circuits)	1 pcs.
422.535110	53x71x11-15 cm (4-5 circuits)	1 pcs.
422.680110	68x71x11-15 cm (6-8 circuits)	1 pcs.
422.835110	83x71x11-15 cm (9-11 circuits)	1 pcs.
422.1035110	103x71x11-15 cm (12-15 circuits)	1 pcs.

Low-depth manifold cabinet



422.435082	43x71x08-13 cm (2-3 circuits)	1 pcs.
422.535082	53x71x08-13 cm (4-5 circuits)	1 pcs.
422.680082	68x71x08-13 cm (6-8 circuits)	1 pcs.
422.835082	83x71x08-13 cm (9-11 circuits)	1 pcs.
422.1035082	103x71x08-13 cm (12-15 circuits)	1 pcs.

1" stainless steel manifolds with automatic drain, eurocone outlets 3/4" M








422.1002	2 circuits	1 pcs.
422.1003	3 circuits	1 pcs.
422.1004	4 circuits	1 pcs.
422.1005	5 circuits	1 pcs.
422.1006	6 circuits	1 pcs.
422.1007	7 circuits	1 pcs.
422.1008	8 circuits	1 pcs.
422.1009	9 circuits	1 pcs.
422.1010	10 circuits	1 pcs.
422.1011	11 circuits	1 pcs.
422.1012	12 circuits	1 pcs.

Composition: Return manifold with thermostatic valves, automatic drain and drain tap. Flow manifold with flowmeter (0.1 to 5 l/min), automatic drain and drain tap. 1" red and blue ball valves with thermometers. Isophonic clamps 3/4" Male plug eurocone outlet. Separation of 50mm outputs. Does not include adapters.



MANIFOLDS AND CABINETS

Reference	Description	Minimum sales pcs
	<p>AIS Air 2-circuit plastic modular manifold kit.</p> <p>422.122</p> <ul style="list-style-type: none"> ▪ Body 1". ▪ Connection to main pipe in 1 1/4" M. ▪ Supply and return circuits 3/4" M. 	1 pcs.
	<p>AIS Air additional circuit module.</p> <p>422.111</p> <ul style="list-style-type: none"> ▪ Body 1". ▪ Connection to supply and return circuits 3/4" M. 	1 pcs.
	<p>Set of 2 ball valves for plastic modular manifold</p> <p>421.114100</p> <p>1 1/4" H swivel fitting - 1" H.</p>	1 pcs.

Reference	Dimensions	Minimum sales pcs	Pallet or pcs per box
			
421.8162034	16 x 2,00 - 3/4"	2 pcs.	50 pcs.
421.8202034	20 x 2,00 - 3/4"	2 pcs.	50 pcs.
			
421.70316	16 x 2,00 - 3/4"	2 pcs.	50 pcs.



MANIFOLDS AND BOXES

Reference	Dimensions	Minimum pcs sale	Pallet or pcs per box
-----------	------------	------------------	-----------------------

Manifold housing boxes for sanitary application



420.901	300x350x90mm	1 pcs.	-
420.902	300x430x90mm	1 pcs.	-
420.903	300x530x90mm	1 pcs	-
420.904	300x630x90mm	1 pcs.	-

Simple manifold for sanitary application with conical seat



420.357342	3/4" x 1/2" M 2outputs	1 pcs.	10 pcs.
420.357343	3/4" x 1/2" M 3outputs	1 pcs.	8 pcs.
420.357344	3/4" x 1/2" M 4outputs	1 pcs.	8 pcs.



NEW

Simple manifold for sanitary application with flat seat

420.305402	3/4" x 1/2" M 2outputs	1 pcs.	6 pcs.
420.305403	3/4" x 1/2" M 3outputs	1 pcs.	5 pcs.

Manifold with regulation valves for sanitary application



420.3TG05402	3/4" x 1/2" M 2outputs	1 pcs.	5 pcs.
420.3TG05403	3/4" x 1/2" M 3outputs	1 pcs.	5 pcs.

Brass blanking cap for sanitary manifold



421.034	3/4" H	1 pcs.	500 pcs.
----------------	--------	--------	----------

Adapter for sanitary and regulation manifold



421.80316	16x2,00 - 1/2"	2 pcs.	250 pcs.
------------------	----------------	--------	----------



MANIFOLDS AND BOXES

Reference	Dimensions	Minimum pcs sale	Pallet or pcs per box
-----------	------------	------------------	-----------------------

Eurocone adapter (exclusively for multilayer tubing)



421.70316	16x2,00 - 3/4"	2 pcs.	200 pcs.
421.70820	20x2,25 - 3/4"	2 pcs.	200 pcs.
421.708201	20x2,00 - 3/4"	2 pcs.	250 pcs.


Jack - Socket Adaptor



421.1234	1/2"H - 3/4"M	1 pcs.	100 pcs.
-----------------	---------------	--------	----------

Reference	Dimensions	Minimum pcs sale
-----------	------------	------------------

1" stainless steel manifolds with drain - eurocone outlets 3/4" M



422.1204	4 outputs 3/4" M	1 pcs.
422.1205	5 outputs 3/4" M	1 pcs.
422.1206	6 outputs 3/4" M	1 pcs.
422.1207	7 outputs 3/4" M	1 pcs.
422.1208	8 outputs 3/4" M	1 pcs.
422.1209	9 outputs 3/4" M	1 pcs.
422.1210	10 outputs 3/4" M	1 pcs.
422.1211	11 outputs 3/4" M	1 pcs.
422.1212	12 outputs 3/4" M	1 pcs.

Reference	Dimensions	Minimum pcs sale	Pallet or pcs per box
-----------	------------	------------------	-----------------------



Red and blue heating manifold ball valves

421.23434	3/4" M-H	1 pcs.	10 pcs.
------------------	----------	--------	---------



AIS TOOLS



Reference	Dimensions	Minimum pcs sale	Pallet or pcs per box
Reusable fitting for pressure test			
360.101612	16x2,00 - 1/2"H	10 pcs.	200 pcs.
360.102012	20x2,25 - 1/2"H	10 pcs.	200 pcs..
360.102512	25x2,50 - 1/2"H	10 pcs.	170 pcs.
360.103212	32x3,00 - 1/2"H	10 pcs.	100 pcs.
360.104012	40x4,00 - 1/2"H	10 pcs.	60 pcs.



Reference	Dimensions	Minimum pcs sale	Pallet or pcs per box
Spare O-ring			
283.16	16mm	10 pcs.	200 pcs.
283.20P	20mm	10 pcs.	200 pcs.
283.25P	25mm	10 pcs.	200 pcs.
283.32P	32mm	10 pcs.	200 pcs.
283.40P	40mm	10 pcs.	200 pcs.



Reference	Dimensions	Minimum pcs sale	Pallet or pcs per box
Attache case 16 to 32mm inserts			
360.1000P	16-32mm	1 pcs.	-



Reference	Description	Minimum pcs sale
Handle for beveling tool		
360.000	Made of stainless steel	1 pcs.



Referencia	Dimensions	Minimum pcs sale
Beveling insert 16 to 75mm		
360.0016	16x2,00	1 pcs.
360.0020	20x2,25/20x200	1 pcs.
360.0025	25x2,50	1 pcs.
360.0032	32x3,00	1 pcs.
360.1040	40x4,00	1 pcs.
360.1050	50x4,50	1 pcs.
360.1063	63x6,00	1 pcs.
360.1075	75x7,50	1 pcs.



AIS TOOLS

Reference	Dimensions	Minimum pcs sale
-----------	------------	------------------



Pipe cutter with calibration arbour

360.61632	16 a 26mm	1 pcs.
------------------	-----------	--------



Spare shear blades

360.616260	-	1 pcs..
-------------------	---	---------

Reference	Dimensions	Minimum pcs sale
-----------	------------	------------------



Cutter for PEX and Multilayer pipe

360.81640	Up to diam. 40mm	1 pcs.
360.81675	Up to diam. 75mm	1 pcs.



Spare blade

360.816400	Up to diam. 40 mm	1 pcs.
360.816750	Up to diam. 75 mm	1 pcs.



Triple beveling tool

360.162025	16 - 20 - 25mm	1 pcs.
-------------------	----------------	--------



Battery Press Machine Box + Machine + Battery + Charger

360.316751	Up to diam 16 a 75mm	1 pcs.
-------------------	----------------------	--------



AIS TOOLS



Reference	Dimensions	Minimum pcs sale
Press Jaws		
360.316	Ø 16	1 psc.
360.320	Ø 20	1 psc.
360.325	Ø 25	1 psc.
360.332	Ø 32	1 psc.
360.340	Ø 40	1 psc.
360.350	Ø 50	1 psc.
360.363	Ø 63	1 psc.
360.375 *	Ø 75	1 psc.

Includes U75 pressing tongs and adapter tongs. They can also be supplied separately. Please check.



Battery Press Machine - Box + Machine + Battery + Charger

360.516321	Up to diam 16 a 40mm	1 psc.
-------------------	----------------------	--------



Mini U Press Jaws

360.516	Ø 16	1 psc.
360.520	Ø 20	1 psc.
360.525	Ø 25	1 psc.
360.532	Ø 32	1 psc.
360.540	Ø 40	1 psc.



Pressure machine battery charger

360.3111	Battery charger	1 psc.
-----------------	-----------------	--------



AIS TOOLS

Reference	Dimensions	Minimum pcs sale
-----------	------------	------------------

Li-ion spare battery 3.0 Ah



360.3121	Battery Li-ion14,4V - 30Ah	1 pcs.
-----------------	----------------------------	--------

Network connection module for press



360.313	Red connection module 230V	1 pcs.
----------------	----------------------------	--------

Reference	Dimensions	Minimum pcs sale
-----------	------------	------------------

Hand crimping tool from 16 to 32mm, U-type jaws



360.41632	Up to 16 a 32mm	1 pcs.
------------------	-----------------	--------

Internal Tubing Bending Spring



360.2016	16x2,00	1 pcs.
360.2020	20x2,25	1 pcs.
360.2025	25x2,50 ó 26x3,00	1 pcs.

External Tubing Bending Spring



360.2116	16x2,00	1 pcs.
360.2120	20x2,25/20x2,00	1 pcs.
360.2125	25x2,50	1 pcs.
360.2132	32x3,00	1 pcs.

Reference	Dimensions	Minimum pcs sale	Pallet or pcs per box
-----------	------------	------------------	-----------------------

NEW

Ergonomic unwinder with rollers and bag




360.1014340	Height 870 - 1122mm Ø ext 1140mm Ø int 360mm	1 ud.	1 pcs..
--------------------	---	-------	---------




**Building the world we
believe in.**

Multicapas Industrial, S.L

 Travesía del Encinar, 3,4,5. Pol Ind Monte Boyal
45950 Casarrubios del Monte (Toledo)

 +34 918 171 8 84  +34 617 430 093

 info@aisoutnovation.com



www.aisoutnovation.com





Building Outnovation

Multicapas Industrial, S.L

Travesía del Encinar, 3,4,5. Pol Ind Monte Boyal

45950 Casarrubios del Monte (Toledo)

info@aisoutnovation.com

www.aisoutnovation.com